

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 03.08.2018

Version number 2

Revision: 08.02.2018

SECTION 1: Identification

- **1.1 Product identifier**
- **Trade name: GC Acrylic Primer**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Auxiliary for dental technology
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
GC EUROPE N.V.
Interleuvenlaan 33
B-3001 Leuven
Tel. +32/(0)16/74.10.00
Fax +32/(0)16/40.26.84
msds@gc.dental
- **Information department:** Regulatory affairs
- **1.4 Emergency telephone number:** International: +01-813-248-0585 (ChemTel Inc.)

SECTION 2: Hazard(s) identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
Exempt from requirements - product regulated as a medical device or an in vitro diagnostic medical device.

Flam. Liq. 2	H225	Highly flammable liquid and vapour.
Skin Irrit. 2	H315	Causes skin irritation.
Eye Irrit. 2	H319	Causes serious eye irritation.
Skin Sens. 1	H317	May cause an allergic skin reaction.
STOT SE 3	H335-H336	May cause respiratory irritation. May cause drowsiness or dizziness.
Aquatic Chronic 3	H412	Harmful to aquatic life with long lasting effects.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
Exempt from requirements - product regulated as a medical device or an in vitro diagnostic medical device.
The product is classified and labeled according to the CLP regulation.
- **Hazard pictograms**



GHS02 GHS07

- **Signal word** Danger
- **Hazard-determining components of labeling:**
Methyl methacrylate
acetone
Urethane Dimethacrylate (UDMA)

(Contd. on page 2)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 03.08.2018

Version number 2

Revision: 08.02.2018

Trade name: GC Acrylic Primer

(Contd. of page 1)

· Hazard statements

- H225 Highly flammable liquid and vapour.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H317 May cause an allergic skin reaction.
 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.
 H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P280 Wear protective gloves / eye protection / face protection.
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P405 Store locked up.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· 2.3 Other hazards**· Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
 · **vPvB:** Not applicable.

* **SECTION 3: Composition/information on ingredients**

· 3.2 Chemical characterization: Mixtures**· Description:**

Only substances required to be mentioned according to Annex II of regulation 1907/2006 are listed. Information on the other substances that may be present can be obtained upon request.

· Dangerous components:

67-64-1	acetone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	25-<50%
80-62-6	Methyl methacrylate Flam. Liq. 2, H225; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	25-<50%
72869-86-4	Urethane Dimethacrylate (UDMA) Skin Sens. 1, H317	10-<25%
128-37-0	Butylated hydroxytoluene Aquatic Acute 1, H400; Aquatic Chronic 1, H410	≥0.25-<0.5%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First-aid measures

· 4.1 Description of first aid measures**· General information:**

Immediately remove any clothing soiled by the product.
 If symptoms persist consult doctor.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
 Take affected persons into fresh air and keep quiet.

(Contd. on page 3)

EU

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 03.08.2018

Version number 2

Revision: 08.02.2018

Trade name: GC Acrylic Primer

(Contd. of page 2)

- **After skin contact:**
Immediately wash with water and soap and rinse thoroughly.
Seek medical treatment.
If skin irritation continues, consult a doctor.
- **After eye contact:**
Protect unharmed eye.
Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:**
Rinse out mouth and then drink plenty of water.
If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** Allergic reactions
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Fire-fighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water
- **5.2 Special hazards arising from the substance or mixture**
Formation of toxic gases is possible during heating or in case of fire.
- **5.3 Advice for firefighters**
- **Protective equipment:** Wear self-contained respiratory protective device.
- **Additional information**
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Remove persons from danger area.
Keep away from ignition sources
Avoid contact with the eyes and skin.
Wear protective clothing.
- **6.2 Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Do not allow to penetrate the ground/soil.
- **6.3 Methods and material for containment and cleaning up:**
Ensure adequate ventilation.
Absorb liquid components with liquid-binding material.
Dispose of the collected material according to regulations.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 03.08.2018

Version number 2

Revision: 08.02.2018

Trade name: GC Acrylic Primer

(Contd. of page 3)

Avoid contact with the eyes and skin.

· **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Do not spray on a naked flame or any incandescent material.

· **7.2 Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:**

Store in a cool location.

Store only in unopened original receptacles.

· **Information about storage in one common storage facility:** Store away from foodstuffs.

· **Further information about storage conditions:**

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

Store in a cool place.

· **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see item 7.

· **8.1 Control parameters**

· **Components with limit values that require monitoring at the workplace:**

67-64-1 acetone

IOELV Long-term value: 1210 mg/m³, 500 ppm

80-62-6 Methyl methacrylate

IOELV Short-term value: 100 ppm
Long-term value: 50 ppm

· **DNELs**

80-62-6 Methyl methacrylate

Dermal DNEL dermal 13.67 mg/kg bw/day (man) (worker, l. te., syst.)

Inhalative DNEL inhalation 208 mg/m³ (air) (worker, l. te., syst.)

128-37-0 Butylated hydroxytoluene

Dermal DNEL dermal 0.5 mg/kg bw/day (man)

Inhalative DNEL inhalation 3.5 mg/m³ (man)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

The usual precautionary measures for handling chemicals should be followed.

Avoid contact with the eyes and skin.

Wash hands before breaks and at the end of work.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

· **Breathing equipment:** Suitable respiratory protective device recommended.

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 03.08.2018

Version number 2

Revision: 08.02.2018

Trade name: GC Acrylic Primer

(Contd. of page 4)

· Protection of hands:

Protective gloves

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:

Tightly sealed goggles

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties**· General Information****· Appearance:**

Form:	Liquid
Color:	Clear
Odor:	Characteristic
Odor threshold:	Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	55 °C

· Flash point: -17 °C

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature: Undetermined.

· Decomposition temperature: Not determined.

· Auto igniting: Product is not selfigniting.

· Danger of explosion: Product does not present an explosion hazard.

· Explosion limits:

Lower:	2.1 Vol %
Upper:	13 Vol %

· Vapor pressure: Not determined.

· Density at 20 °C:	0.9 g/cm ³
· Relative density	Not determined.
· Vapor density	Not determined.

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 03.08.2018

Version number 2

Revision: 08.02.2018

Trade name: GC Acrylic Primer

(Contd. of page 5)

· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Insoluble.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	48.5 %
VOC (EC)	436.7 g/l
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity:** Based on available data, the classification criteria are not met.

· LD/LC50 values that are relevant for classification:		
67-64-1 acetone		
Oral	LD50	5,800 mg/kg (rat (f+m))
Dermal	LD50	20,000 mg/kg (rabbit)
80-62-6 Methyl methacrylate		
Oral	LD50	6,000 mg/kg (rabbit)
Dermal	LD50	>5,000 mg/kg (rab)
Inhalative	LC50/4 h	29.8 mg/l (rat (f+m))
72869-86-4 Urethane Dimethacrylate (UDMA)		
Oral	LD50	>5,000 mg/kg (rat female) (OECD 401)
128-37-0 Butylated hydroxytoluene		
Oral	LD50	>6,000 mg/kg (rat (f+m)) (OECD 401)

- **Primary irritant effect:**
- **on the skin:**
Causes skin irritation.
- **on the eye:**
Causes serious eye irritation.
- **Sensitization:**
May cause an allergic skin reaction.

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 03.08.2018

Version number 2

Revision: 08.02.2018

Trade name: GC Acrylic Primer

(Contd. of page 6)

· **Additional toxicological information:**· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

- **Repeated dose toxicity** No further relevant information available.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
No further relevant information available.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause respiratory irritation. May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

* **SECTION 12: Ecological information**· **12.1 Toxicity**· **Aquatic toxicity:****72869-86-4 Urethane Dimethacrylate (UDMA)**

EC50/48h (static) >1.2 mg/l (daphnia magna) (OECD 202)

128-37-0 Butylated hydroxytoluene

EC50/48h (static) 0.48 mg/l (daphnia magna) (OECD 202)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
Harmful to aquatic organisms
Water hazard class 1 (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

EU
(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 03.08.2018



Version number 2

Revision: 08.02.2018

Trade name: GC Acrylic Primer

(Contd. of page 7)

SECTION 14: Transport information

· 14.1 UN-Number · ADR, IMDG, IATA	UN1993
· 14.2 UN proper shipping name · DOT · ADR · IMDG, IATA	Flammable liquids, n.o.s. (Acetone, Methyl methacrylate monomer, stabilized) 1993 FLAMMABLE LIQUID, N.O.S. (ACETONE, METHYL METHACRYLATE MONOMER, STABILIZED), special provision 640D FLAMMABLE LIQUID, N.O.S. (ACETONE, METHYL METHACRYLATE MONOMER, STABILIZED)
· 14.3 Transport hazard class(es) · ADR	
	
· Class · Label	3 (F1) Flammable liquids 3
· IMDG, IATA	
	
· Class · Label	3 Flammable liquids 3
· 14.4 Packing group · ADR, IMDG, IATA	II
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user · Danger code (Kemler): · EMS Number: · Stowage Category	Warning: Flammable liquids 33 F-E, S-E B
· 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· Transport category · Tunnel restriction code	2 D/E

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 03.08.2018

Version number 2

Revision: 08.02.2018

Trade name: GC Acrylic Primer

(Contd. of page 8)

· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1993 FLAMMABLE LIQUID, N.O.S., SPECIAL PROVISION 640D (ACETONE, METHYL METHACRYLATE MONOMER, STABILIZED), 3, II

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

- **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

- **Section 313 (Specific toxic chemical listings):**

80-62-6 Methyl methacrylate

- **Proposition 65**

- **Chemicals known to cause cancer:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

- **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

- **Carcinogenic categories**

- **EPA (Environmental Protection Agency)**

67-64-1	acetone	I
80-62-6	Methyl methacrylate	E, NL

- **TLV (Threshold Limit Value established by ACGIH)**

67-64-1	acetone	A4
80-62-6	Methyl methacrylate	A4
128-37-0	Butylated hydroxytoluene	A4

- **MAK (German Maximum Workplace Concentration)**

128-37-0	Butylated hydroxytoluene	4
----------	--------------------------	---

- **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

- **Directive 2012/18/EU**

- **Named dangerous substances - ANNEX I** None of the ingredients is listed.

- **Seveso category P5c** FLAMMABLE LIQUIDS

- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t

- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t

(Contd. on page 10)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 03.08.2018

Version number 2

Revision: 08.02.2018

Trade name: GC Acrylic Primer

(Contd. of page 9)

- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

- **Relevant phrases**

- H225 Highly flammable liquid and vapour.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.

- **Classification according to Regulation (EC) No 1272/2008** Calculation method

- **Department issuing SDS:** Regulatory affairs

- **Contact:** msds@gc.dental

- **Abbreviations and acronyms:**

- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- DOT: US Department of Transportation
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- ACGIH: American Conference of Governmental Industrial Hygienists
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- DNEL: Derived No-Effect Level (REACH)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- NIOSH: National Institute for Occupational Safety
- OSHA: Occupational Safety & Health
- Flam. Liq. 2: Flammable liquids – Category 2
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
- Skin Sens. 1: Skin sensitisation – Category 1
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
- Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
- Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

- **Sources**

- ECHA (<http://echa.europa.eu/>)
- EnviChem (www.echemportal.org)

- *** Data compared to the previous version altered.**

This version replaces all previous versions.

Disclaimer:

The information contained herein is believed to be true and accurate. However, all statements, recommendations or suggestions are made without any guarantee, representation or warranty, express or implied, on our part. Therefore, no warranty is made or to be implied that the information set out in this document is accurate or complete, and we accordingly exclude all liability in connection with the use of this information or the products referred to herein. All such risks are assumed by the purchaser/user. The information contained herein is also subject to change without notice. For the avoidance of doubt, however, nothing in this document excludes or limits our liability for death or personal injury caused by our negligence or for fraudulent misrepresentation.

(Contd. on page 11)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 03.08.2018

Version number 2

Revision: 08.02.2018

Trade name: GC Acrylic Primer

(Contd. of page 10)