



Safety Data Sheet

acc. to OSHA HCS

Printing date 03/16/2015

Version CA-EN-Rev 1

Reviewed on 03/16/2015

1 Identification

- **Product identifier**

- **Trade name:** UNIFAST LC (Liquid)

- **Relevant identified uses of the substance or mixture and uses advised against**

Dental material

The product is intended for professional use.

To avoid risks for humans and environment obtain instructions.

- **Application of the substance / the mixture** Manufacture of dental prothesis

- **Details of the supplier of the safety data sheet**

- **Manufacturer/Supplier:**

GC America Inc.

3737 W. 127th Street

Alsip, IL 60803

USA

sds@gcamerica.com

- **Information department:** Regulatory Affairs

- **Emergency telephone number:**

During normal opening times (Mon.-Fri. 8:00 AM-5:00 PM CST): +1 (708) 597-0900

Transportation (CHEMTREC®) Emergency Telephone No. +1 (800) 424-9300

2 Hazard(s) identification

- **Classification of the substance or mixture**

Flam. Liq. 2 H225 Highly flammable liquid and vapor.

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**

Irritant

Irritating to respiratory system and skin. May cause sensitization by skin contact.

Highly flammable

Highly flammable.

- **Classification system:**

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

- **Additional information:**

The information provided is in regards to the toxicity and hazard rating(s) of the individual component(s) in the formulation. The associated risk(s) depends on the route(s) of exposure. The hazard rating system is based entirely on the existence of the risk(s) and does not take into account the likelihood of reduced risk(s) through proper usage and handling.

- **Label elements**

- **Labelling according to EU guidelines:**

The product has been classified and marked in accordance with directives on hazardous materials.

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/16/2015

Version CA-EN-Rev 1

Reviewed on 03/16/2015

Trade name: UNIFAST LC (Liquid)

(Contd. of page 1)

· **Code letter and hazard designation of product:**



Irritant
Highly flammable

· **Hazard-determining components of labeling:**

methyl methacrylate (MMA)
urethane dimethacrylate (UDMA)

· **Risk phrases:**

Highly flammable.
Irritating to respiratory system and skin.
May cause sensitization by skin contact.

· **Safety phrases:**

Keep container in a well-ventilated place.
Keep away from sources of ignition - No smoking.
Do not breathe gas/fumes/vapour/spray.
Avoid contact with skin.
Wear suitable gloves.
This material and its container must be disposed of as hazardous waste.

· **Hazard description:**

· **WHMIS-symbols:**

B2 - Flammable liquid
D2B - Toxic material causing other toxic effects



· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 2
Fire = 3
Reactivity = 2

· **HMIS-ratings (scale 0 - 4)**



Health = 2
Fire = 3
Reactivity = 2

· **Other hazards**

· **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

- **Description:** Mixture of the substances listed below with nonhazardous additions.

(Contd. on page 3)

CA

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/16/2015

Version CA-EN-Rev 1

Reviewed on 03/16/2015

Trade name: UNIFAST LC (Liquid)

(Contd. of page 2)

- **Dangerous components:**

| | | |
|------------|--------------------------------|--------|
| 80-62-6 | methyl methacrylate (MMA) | 30-60% |
| 72869-86-4 | urethane dimethacrylate (UDMA) | 10-30% |

- **Additional information:**

If a substance is marked with **, then substance is a trade secret. This is allowed under OSHA's Hazard Communication Standard (HCS) as a trade secret and under GHS as Confidential Business Information (CBI).

4 First-aid measures

- **Description of first aid measures**

- **General information:**

Immediately remove any clothing soiled by the product.
If symptoms persist consult doctor.

- **After inhalation:**

Supply fresh air; consult doctor in case of complaints.
In case of unconsciousness place patient stably in side position for transportation.

- **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.
Seek medical treatment.

- **After eye contact:**

Rinse opened eye for several minutes under running water.
If symptoms persist consult doctor.

- **After swallowing:**

Rinse out mouth and then drink plenty of water.
If symptoms persist consult doctor.

- **Information for doctor:**

- **Most important symptoms and effects, both acute and delayed** Allergic reactions

- **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**

- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.

- **For safety reasons unsuitable extinguishing agents:** Water

- **Special hazards arising from the substance or mixture**

In case of fire, the following can be released:

Nitrogen oxides (NO_x)

Carbon monoxide (CO)

Carbon monoxide and carbon dioxide

Carbon dioxide

- **Advice for firefighters**

- **Protective equipment:** Wear self-contained respiratory protective device.

- **Additional information**

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

CA

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/16/2015

Version CA-EN-Rev 1

Reviewed on 03/16/2015

Trade name: UNIFAST LC (Liquid)

(Contd. of page 3)

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
 - Remove persons from danger area.
 - Keep away from ignition sources
 - Avoid contact with the eyes and skin.
 - Wear protective clothing.
- **Environmental precautions:**
 - Do not allow product to reach sewage system or any water course.
 - Inform respective authorities in case of seepage into water course or sewage system.
 - Do not allow to penetrate the ground/soil.
 - In case of seepage into the ground inform responsible authorities.
- **Methods and material for containment and cleaning up:**
 - Ensure adequate ventilation.
 - Absorb liquid components with liquid-binding material.
 - Dispose of the collected material according to regulations.
- **Reference to other sections**
 - See Section 7 for information on safe handling.
 - See Section 8 for information on personal protection equipment.
 - See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
 - Observe instructions for use.
 - Ensure good ventilation/exhaustion at the workplace.
 - Prevent formation of aerosols.
 - Avoid contact with the eyes and skin.
- **Information about protection against explosions and fires:**
 - Keep ignition sources away - Do not smoke.
 - Protect against electrostatic charges.
 - Do not spray on a naked flame or any incandescent material.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
 - Store in a cool location.
 - Store only in unopened original receptacles.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:**
 - Observe instructions for use / storage.
 - Keep receptacle tightly sealed.
 - Store in cool, dry conditions in well sealed receptacles.
 - Protect from heat and direct sunlight.
 - Store in a cool place.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

(Contd. on page 5)

-CA

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/16/2015

Version CA-EN-Rev 1

Reviewed on 03/16/2015

Trade name: UNIFAST LC (Liquid)

(Contd. of page 4)

- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

80-62-6 methyl methacrylate (MMA)

| | |
|----|---|
| EL | Short-term value: 100 ppm Long-term value: 50 ppm S |
|----|---|

| | |
|----|--|
| EV | Short-term value: 100 ppm Long-term value: 50 ppm |
|----|--|

- **Additional information:** The lists that were valid during the creation were used as basis.

- **Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

The usual precautionary measures for handling chemicals should be followed.

Avoid contact with the eyes and skin.

Wash hands before breaks and at the end of work.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

- **Breathing equipment:** Suitable respiratory protective device recommended.

- **Protection of hands:** Protective gloves

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:** Safety glasses

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form: Liquid

Color: Clear

- **Odor:** Characteristic

- **Odor threshold:** Not determined.

- **pH-value:** Not determined.

- **Change in condition**

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: 100 °C

- **Flash point:** 10 °C

- **Flammability (solid, gaseous):** Not applicable.

- **Ignition temperature:** Undetermined.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/16/2015

Version CA-EN-Rev 1

Reviewed on 03/16/2015

Trade name: UNIFAST LC (Liquid)

(Contd. of page 5)

| | |
|---|---|
| · Decomposition temperature: | Not determined. |
| · Auto igniting: | Product is not selfigniting. |
| · Danger of explosion: | Heating may cause an explosion. Product is not explosive. However, formation of explosive air/ vapor mixtures are possible. |
| · Explosion limits: | |
| Lower: | 2.1 Vol % |
| Upper: | 12.5 Vol % |
| · Vapor pressure: | Not determined. |
| · Density at 20 °C: | 0.9 g/cm ³ |
| · Relative density | Not determined. |
| · Vapour density | Not determined. |
| · Evaporation rate | Not determined. |
| · Solubility in / Miscibility with Water: | Insoluble. |
| · Partition coefficient (n-octanol/water): | Not determined. |
| · Viscosity: | |
| Dynamic: | Not determined. |
| Kinematic: | Not determined. |
| · Solvent content: | |
| Organic solvents: | 0.0 % |
| · Other information | No further relevant information available. |

10 Stability and reactivity

- **Reactivity** Danger of polymerization.
- **Chemical stability** Stable at ambient temperature.
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions**
Spontaneous polymerization can be caused in unstabilized product e.g. by ambient heat.
Danger of receptacles bursting because of high vapor pressure if heated.
Exothermic polymerization.
Reacts with reducing agents.
Reacts with alkali (lyes).
Reacts with acids.
Reacts with oxidizing agents.
- **Conditions to avoid** Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- **Incompatible materials:**
Reacts with oxidizing agents.
Reacts with reducing agents.
Reacts with peroxides and other radical forming substances.
Reacts with amines.
Reacts with heavy metals.
Reacts with acids.
Reacts with alkali (lyes).

(Contd. on page 7)

CA

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/16/2015

Version CA-EN-Rev 1

Reviewed on 03/16/2015

Trade name: UNIFAST LC (Liquid)

(Contd. of page 6)

- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **LD/LC50 values that are relevant for classification:** No further relevant information available.
- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** No irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Experience with humans:**
 - May cause damage to kidneys.
 - May cause damage to liver.
- **Additional toxicological information:**
 - The product shows the following dangers according to internally approved calculation methods for preparations:
 - Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

methyl methacrylate (MMA)

3

butylated hydroxytoluene (BHT)

3

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

- **Carcinogenic categories' legend:**

IARC Group 1: The agent is carcinogenic to humans.

IARC Group 2A: The agent is probably carcinogenic to humans.

IARC Group 2B: The agent is possibly carcinogenic to humans.

IARC Group 3: The agent is not classifiable as to its carcinogenicity to humans.

IARC Group 4: The agent is probably not carcinogenic to humans.

NTP K: Known to be human carcinogen.

NTP R: Reasonably anticipated to be human carcinogen.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

(Contd. on page 8)

CA

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/16/2015

Version CA-EN-Rev 1

Reviewed on 03/16/2015

Trade name: UNIFAST LC (Liquid)




(Contd. of page 7)

- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|---|---|
| · UN-Number | |
| · DOT, TDG, IMDG, IATA | UN1247 |
| · UN proper shipping name | |
| · DOT | Methyl methacrylate monomer, stabilized solution |
| · TDG | 1247 Methyl methacrylate monomer, stabilized solution |
| · IMDG, IATA | METHYL METHACRYLATE MONOMER, STABILIZED solution |
| · Transport hazard class(es) | |
| · DOT | |
| |  |
| · Class | 3 Flammable liquids |
| · Label | 3 |
| · TDG (Transport dangerous goods): | |
| |  |
| · Class | 3 (F1) Flammable liquids |
| · Label | 3 |
| · IMDG, IATA | |
| |  |
| · Class | 3 Flammable liquids |
| · Label | 3 |

(Contd. on page 9)

CA

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/16/2015

Version CA-EN-Rev 1

Reviewed on 03/16/2015

Trade name: UNIFAST LC (Liquid)

(Contd. of page 8)

| | |
|---|---|
| · Packing group · DOT, TDG, IMDG, IATA | II |
| · Environmental hazards: · Marine pollutant: | No |
| · Special precautions for user · Danger code (Kemler): · EMS Number: | Warning: Flammable liquids 339 F-E,S-D |
| · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |
| · Transport/Additional information: | |
| · TDG · Excepted quantities (EQ) | Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml |
| · IMDG · Limited quantities (LQ) · Excepted quantities (EQ) | 1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml |
| · UN "Model Regulation": | UN1247, Methyl methacrylate monomer, stabilized solution, 3, II |

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- SARA (Superfund Amendments and Reauthorization Act)

- **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

- **Section 313 (Specific toxic chemical listings):**

methyl methacrylate (MMA)

- **TSCA (Toxic Substances Control Act):**

methyl methacrylate (MMA)

urethane dimethacrylate (UDMA)

synergist**

- **Carcinogenic categories**

- **EPA (Environmental Protection Agency)**

methyl methacrylate (MMA)

E, NL

- **TLV (Threshold Limit Value established by ACGIH)**

methyl methacrylate (MMA)

A4

butylated hydroxytoluene (BHT)

A4

- **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

(Contd. on page 10)

CA

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/16/2015

Version CA-EN-Rev 1

Reviewed on 03/16/2015

Trade name: UNIFAST LC (Liquid)

(Contd. of page 9)

- **Canadian substance listings:**

- **Canadian Domestic Substances List (DSL)**

methyl methacrylate (MMA)

synergist**

photoinitiator**

UV-light absorber**

butylated hydroxytoluene (BHT)

- **Canadian Ingredient Disclosure list (limit 0.1%)**

None of the ingredients is listed.

- **Canadian Ingredient Disclosure list (limit 1%)**

methyl methacrylate (MMA)

- **Product related hazard informations:**

The product has been classified and marked in accordance with directives on hazardous materials.

- **Hazard symbols:**

Irritant
Highly flammable

- **Hazard-determining components of labeling:**

methyl methacrylate (MMA)

urethane dimethacrylate (UDMA)

- **Risk phrases:**

Highly flammable.

Irritating to respiratory system and skin.

May cause sensitization by skin contact.

- **Safety phrases:**

Keep container in a well-ventilated place.

Keep away from sources of ignition - No smoking.

Do not breathe gas/fumes/vapour/spray.

Avoid contact with skin.

Wear suitable gloves.

This material and its container must be disposed of as hazardous waste.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

- **Department issuing SDS:** Regulatory Affairs

- **Contact:**

Regulatory Affairs

Telephone No. +1 (708) 597-0900

sds@gcamerica.com

- **Date of preparation / last revision** 03/16/2015 / -

- **Abbreviations and acronyms:**

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

HCS: Hazard Communication Standard (USA)

MSDS: Material Safety Data Sheet

SDS: Safety Data Sheet

(Contd. on page 11)

CA

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/16/2015

Version CA-EN-Rev 1

Reviewed on 03/16/2015

Trade name: UNIFAST LC (Liquid)

(Contd. of page 10)

ECHA: European Chemicals Agency
OSHA: Occupational Safety and Health Administration (USA)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
ACGIH: American Conference of Governmental Industrial Hygienists
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
WHMIS: Workplace Hazardous Materials Information System (Canada)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 2: Flammable liquids, Hazard Category 2
Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
Skin Sens. 1: Sensitisation - Skin, Hazard Category 1
STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

Sources

- Manufacturers' MSDSs/SDSs
- OSHA (<https://www.osha.gov/dts/chemicalsampling/toc/chmcas.html>)
- TOXNET (<http://toxnet.nlm.nih.gov/>)
- ECHA (<http://echa.europa.eu/>)
- EnviChem (www.echemportal.org)

Notes:

CAS Registry Number is a Registered Trademark of the American Chemical Society.
CHEMTREC® is a registered service mark of the American Chemistry Council, Inc.

- * **Data compared to the previous version altered.** This version replaces all previous versions.

Disclaimer:

The information contained herein is believed to be true and accurate. However, all statements, recommendations or suggestions are made without any guarantee, representation or warranty, express or implied, on our part. Therefore, no warranty is made or to be implied that the information set out in this document is accurate or complete, and we accordingly exclude all liability in connection with the use of this information or the products referred to herein. All such risks are assumed by the purchaser/user. The information contained herein is also subject to change without notice. For the avoidance of doubt, however, nothing in this document excludes or limits our liability for death or personal injury caused by our negligence or for fraudulent misrepresentation.