



MS440003

GC TION, WHITENING LIQUID

Page 2 of 2

SECTION 6 - HEALTH HAZARD DATA and FIRST AID INFORMATION - continued

ROUTES OF ENTRY: Inhalation Skin Ingestion

HEALTH HAZARD (Acute and Chronic): Miniscule amount swallowed during proper use should not cause injury. Ingestion of large amount may cause irritation of the upper GI tract with pain and distention of the stomach and esophagus due to the liberation of oxygen.

SIGNS AND SYMPTOMS OF OVEREXPOSURE: Overexposure by contact may cause mild to severe irritation of burns to skin, eyes and mucous membranes. Splashes in the eye may cause damage with ulceration of the cornea, prolonged contact may cause irreversible eye damage including blindness.

CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: N.E.

EMERGENCY FIRST AID PROCEDURES:

INHALATION: If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek medical attention immediately.

EYE CONTACT: Immediately flush eyes with plenty of water for at least 15 minutes, lifting lower and upper eyelids occasionally. Seek medical attention immediately.

SKIN CONTACT: Immediately flush skin with plenty of soap and water for at least 15 minutes.

INGESTION: Do not induce vomiting. Give plenty of water. Never give anything by mouth to an unconscious person. Seek medical attention if abdominal discomfort persists.

SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE

IN CASE OF RELEASE OR SPILL: For small spills, collect material and dispose per federal, state and local regulations. For larger spills (CERLA reportable quantity is 100 lbs for unlisted hazardous waste), isolate area which may present a slip hazard. Sweep or collect material and dispose.

WASTE DISPOSAL METHOD: Dispose of in accordance with local, state and federal guidelines.

STORAGE, HANDLING, AND SPECIAL PRECAUTIONS: Store in a cool, well-ventilated dark area separated from combustible substances, reducing agents, strong bases, and organics. Protect containers from physical damage, contamination, heat and incompatibles. Contamination from any source (dust, metals) may cause rapid decomposition with generation of large quantities of oxygen gas and high pressures.

SECTION 8 - CONTROL MEASURES

RESPIRATORY PROTECTION: Recommended to use a supplied air, full face piece respirator, airlined hood, or full face piece self-contained breathing apparatus.

VENTILATION: Local Exhaust Mechanical: Special: Other:

PROTECTIVE GLOVES: Disposable vinyl gloves recommended.

EYE PROTECTION: Use chemical safety goggles and/or a full face shield where splashing is possible. Maintain eye wash fountain and quick-drench facilities in work area.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate to prevent skin contact.

WORK/HYGIENIC PRACTICE: Observe good hygienic work practices.

SECTION 9 - PREPARATION INFORMATION

This data is supplied to comply with OSHA Hazard Communication Standard 29 CFR 1910,1200 and W.H.M.I.S. CPR.

DATE: 16 April 2007

REVIEWED: 22 January 2009

N.A. = NOT APPLICABLE
N.E. = NOT ESTABLISHED

The information herein is given in good faith but no warranty expressed or implied is made.

FIRE - 0	TOXICITY - 2	NFPA REACTIVITY - 1	SPECIAL - CORR
----------	--------------	------------------------	----------------