



Safety Data Sheet

according to HPR, Schedule 1

Printing date 05/13/2019

Version CA-EN-Rev 1

Reviewed on 05/13/2019

1 Identification

- **Product identifier**

- **Trade name:** GC Acrylic Primer

- **Relevant identified uses of the substance or mixture and uses advised against**

Dental material

The product is intended for professional use.

To avoid risks for humans and environment obtain instructions.

- **Application of the substance / the mixture** Dental bonding material

- **Details of the supplier of the safety data sheet**

- **Manufacturer/Supplier:**

GC America Inc.

3737 W. 127th Street

Alsip, IL 60803

USA

SDS.gcamerica@gc.dental

- **Information department:** Regulatory Affairs

- **Emergency telephone number:**

During normal opening times (Monday–Friday 8:00 AM–5:00 PM Central Time): +1 (708) 597-0900

Transportation (CHEMTREC®) Emergency Telephone No. +1 (800) 424-9300

2 Hazard identification

- **Classification of the substance or mixture**

Exempt from classification and labeling – devices and drugs are not regulated according to WHMIS 2015.

Flammable Liquids - Category 2	H225	Highly flammable liquid and vapour.
Skin Irritation - Category 2	H315	Causes skin irritation.
Eye Irritation - Category 2A	H319	Causes serious eye irritation.
Skin Sensitizer - Category 1	H317	May cause an allergic skin reaction.
Specific Target Organ Toxicity - Single Exposure - Category 3	H335-H336	May cause respiratory irritation. May cause drowsiness or dizziness.
Specific Target Organ Toxicity - Repeated Exposure - Category 1	H372	Causes damage to organs through prolonged or repeated exposure.
Aspiration Hazard - Category 1	H304	May be fatal if swallowed and enters airways.

- **Additional information:**

The information provided is in regards to the toxicity and hazard rating(s) of the individual component(s) in the formulation. The associated risk(s) depends on the route(s) of exposure. The hazard rating system is based entirely on the existence of the risk(s) and does not take into account the likelihood of reduced risk(s) through proper usage and handling.

- **Label elements**

- **GHS label elements**

Exempt from classification and labeling – devices and drugs are not regulated according to WHMIS 2015.

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Safety Data Sheet

according to HPR, Schedule 1

Printing date 05/13/2019

Version CA-EN-Rev 1

Reviewed on 05/13/2019

Trade name: GC Acrylic Primer

(Contd. of page 1)

- **Hazard pictograms**



- **Signal word** Danger

- **Hazard-determining components of labeling:**

acetone
methyl methacrylate (MMA)
urethane dimethacrylate (UDMA)

- **Hazard statements**

Highly flammable liquid and vapour.
Causes skin irritation.
Causes serious eye irritation.
May cause an allergic skin reaction.
May cause respiratory irritation. May cause drowsiness or dizziness.
Causes damage to organs through prolonged or repeated exposure.
May be fatal if swallowed and enters airways.

- **Precautionary statements**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Do not breathe dust/fume/gas/mist/vapours/spray.
Wear protective gloves/protective clothing/eye protection/face protection.
If swallowed: Immediately call a poison center/doctor.
Specific treatment (see on this label).
Do NOT induce vomiting.
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Take off contaminated clothing and wash it before reuse.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Additional information:**

7.9 % of the mixture consists of an ingredient or ingredients of unknown acute toxicity.

- **Physical Hazards Not Otherwise Classified – Category 1** Exothermic polymerization.

3 Composition/Information on ingredients

- **Chemical characterization: Mixtures**

- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 67-64-1	acetone	30 – 60% w/w
CAS: 80-62-6	methyl methacrylate (MMA)	10 – 30% w/w
CAS: 72869-86-4	urethane dimethacrylate (UDMA)	7 – 13% w/w
CAS: 128-37-0	butylated hydroxytoluene	0.1 – 1% w/w

- **Additional information:**

If a substance is marked with **, then substance is a trade secret. This is allowed under OSHA's Hazard Communication Standard (HCS) as a trade secret and under GHS as Confidential Business Information (CBI).

CA

(Contd. on page 3)

Safety Data Sheet

according to HPR, Schedule 1

Printing date 05/13/2019

Version CA-EN-Rev 1

Reviewed on 05/13/2019

Trade name: GC Acrylic Primer

(Contd. of page 2)

4 First aid measures

- **Description of first aid measures**
- **General information:**
Immediately remove any clothing soiled by the product.
If symptoms persist consult doctor.
- **After inhalation:**
Supply fresh air; consult doctor in case of complaints.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:**
Immediately wash with water and soap and rinse thoroughly.
Seek medical treatment.
- **After eye contact:**
Protect unharmed eye.
Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:**
Rinse out mouth and then drink plenty of water.
If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** Allergic reactions
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Firefighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water
- **Special hazards arising from the substance or mixture**
Formation of toxic gases is possible during heating or in case of fire.
No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** Wear self-contained respiratory protective device.
- **Additional information**
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Remove persons from danger area.
Keep away from ignition sources
Avoid contact with the eyes and skin.
Wear protective clothing.
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Do not allow to penetrate the ground/soil.
- **Methods and material for containment and cleaning up:**
Ensure adequate ventilation.
Absorb liquid components with liquid-binding material.
Dispose of the collected material according to regulations.

(Contd. on page 4)

CA

Safety Data Sheet

according to HPR, Schedule 1

Printing date 05/13/2019

Version CA-EN-Rev 1

Reviewed on 05/13/2019

Trade name: GC Acrylic Primer

(Contd. of page 3)

· **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· **Handling:**

· **Precautions for safe handling**

Observe instructions for use.

Ensure good ventilation/exhaustion at the workplace.

Do not inhale dust / smoke / mist.

Prevent formation of aerosols.

Avoid contact with the eyes and skin.

Use caution when opening. The product is a highly flammable liquid and vapor; keep away from heat, hot surfaces, sparks, flames and other ignitions sources. Use with adequate ventilation. Do not ingest or breathe vapor. Personal Protective Equipment (PPE) such as gloves and safety eyewear are always to be worn. Check bottle with liquid before using. Make sure that upon removal of cap, the bottle opening has no obstructions. Some bottles may contain an insert (as a seal). The insert must be in the cap and not obstructing opening.

In case of contact, flush eyes with water for at least 15 minutes. Get prompt medical attention. If overcome by vapor, move to fresh air. If breathing is difficult, administer oxygen and seek medical attention. If swallowed, dilute by giving water to drink and seek medical attention. In case of contact with skin wash thoroughly with soap and water. Store securely. Store in a well ventilated place. Keep cool. Dispose of all waste according to local regulations.

· **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Do not spray on a naked flame or any incandescent material.

· **Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:**

Store in a cool location.

Store only in unopened original receptacles.

· **Information about storage in one common storage facility:** Store away from foodstuffs.

· **Further information about storage conditions:**

Observe instructions for use / storage.

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

Store in a cool place.

· **Specific end use(s)** No further relevant information available.

8 Exposure controls/ Personal protection

· **Additional information about design of technical systems:** No further data; see item 7.

(Contd. on page 5)

Safety Data Sheet

according to HPR, Schedule 1

Printing date 05/13/2019

Version CA-EN-Rev 1

Reviewed on 05/13/2019

Trade name: GC Acrylic Primer

(Contd. of page 4)

- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

CAS: 67-64-1 acetone

EL	Short-term value: 500 ppm Long-term value: 250 ppm
EV	Short-term value: 750 ppm Long-term value: 500 ppm

CAS: 80-62-6 methyl methacrylate (MMA)

EL	Short-term value: 100 ppm Long-term value: 50 ppm S(D)
EV	Short-term value: 100 ppm Long-term value: 50 ppm

- **Additional information:** The lists that were valid during the creation were used as basis.

- **Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

The usual precautionary measures for handling chemicals should be followed.

Avoid contact with the eyes and skin.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

- **Breathing equipment:**



Suitable respiratory protective device recommended.

- **Protection of hands:**



Protective gloves

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Safety glasses

CA

(Contd. on page 6)

Safety Data Sheet

according to HPR, Schedule 1

Printing date 05/13/2019

Version CA-EN-Rev 1

Reviewed on 05/13/2019

Trade name: GC Acrylic Primer

(Contd. of page 5)

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form:	Liquid
Color:	Light yellow
· Odor:	Acetone-like
· Odor threshold:	Not determined.

- pH-value: Not determined.

- **Change in condition**

Melting point/Melting range:	-94.6 °C
Boiling point/Boiling range:	56.2 – 56.5 °C

- Flash point: -16 °C

- Flammability (solid, gaseous): Not applicable.

- Ignition temperature: Undetermined.

- Decomposition temperature: Not determined.

- Auto igniting: Product is not self-igniting.

- **Danger of explosion:** Heating may cause an explosion. Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

- **Explosion limits:**

Lower:	Not determined.
Upper:	2.1 Vol %

- Vapor pressure: Not determined.

- Density: Not determined.

- Relative density: Not determined.

- Vapor density: Not determined.

- Evaporation rate: Not determined.

- **Solubility in / Miscibility with**

Water:	Insoluble.
--------	------------

- Partition coefficient (n-octanol/water): Not determined.

- **Viscosity:**

Dynamic:	Not determined.
Kinematic:	Not determined.

- **Solvent content:**

Organic solvents:	49.0 %
-------------------	--------

- **Other information** No further relevant information available.

10 Stability and reactivity

- **Reactivity** Danger of polymerization.
- **Chemical stability** Stable at ambient temperature.

(Contd. on page 7)

Safety Data Sheet

according to HPR, Schedule 1

Printing date 05/13/2019

Version CA-EN-Rev 1

Reviewed on 05/13/2019

Trade name: GC Acrylic Primer

(Contd. of page 6)

- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions**
Spontaneous polymerization can be caused in unstabilized product e.g. by ambient heat.
Danger of receptacles bursting because of high vapor pressure if heated.
Exothermic polymerization.
- **Conditions to avoid**
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- **Incompatible materials:**
Reacts with peroxides and other radical forming substances.
Reacts with amines.
Reacts with heavy metals.
- **Hazardous decomposition products:**
Carbon dioxide
Carbon monoxide

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

CAS: 128-37-0 butylated hydroxytoluene

Oral	LD50	10,700 mg/kg (guinea pig) 1,040 mg/kg (mouse) 2,930 mg/kg (rat (f+m))
Dermal	LD50	890 mg/kg (rat (f+m))

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** Sensitization possible through skin contact.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

methyl methacrylate (MMA)	3
butylated hydroxytoluene	3

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **Carcinogenic categories' legend:**

IARC Group 1: The agent is carcinogenic to humans.
IARC Group 2A: The agent is probably carcinogenic to humans.
IARC Group 2B: The agent is possibly carcinogenic to humans.
IARC Group 3: The agent is not classifiable as to its carcinogenicity to humans.
IARC Group 4: The agent is probably not carcinogenic to humans.
NTP K: Known to be human carcinogen.
NTP R: Reasonably anticipated to be human carcinogen.

(Contd. on page 8)

Safety Data Sheet

according to HPR, Schedule 1

Printing date 05/13/2019

Version CA-EN-Rev 1

Reviewed on 05/13/2019

Trade name: GC Acrylic Primer

(Contd. of page 7)

- **Repeated dose toxicity.** No further relevant information available.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
No further relevant information available.

12 Ecological information

- **Toxicity**

- **Aquatic toxicity:**

CAS: 128-37-0 butylated hydroxytoluene

NOEC-value Ecol. other effects	0.07 mg/l (daphnia magna) 21 day, reproductive effects
--------------------------------	---

- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (German regulation, AwSV) (Self-assessment): slightly hazardous to water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Harmful to aquatic organisms
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Dispose of contents / container in accordance with local / regional / national / international regulations.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|-----------------------------------|-----------------------|
| · UN-Number | |
| · DOT/TDG, ADR, IMDG, IATA | UN1090 |
| · UN proper shipping name | |
| · DOT/TDG | Acetone solution |
| · ADR | 1090 ACETONE solution |
| · IMDG, IATA | ACETONE solution |

(Contd. on page 9)

CA

Safety Data Sheet

according to HPR, Schedule 1

Printing date 05/13/2019

Version CA-EN-Rev 1

Reviewed on 05/13/2019

Trade name: GC Acrylic Primer

(Contd. of page 8)

- **Transport hazard class(es)**

- **DOT/TDG (Transport dangerous goods):**



- **Class** 3 Flammable liquids
- **Label** 3

- **ADR**



- **Class** 3 (F1) Flammable liquids
- **Label** 3

- **IMDG, IATA**



- **Class** 3 Flammable liquids
- **Label** 3

- **Packing group**

- **DOT/TDG, ADR, IMDG, IATA** II

- **Environmental hazards:** Not applicable.

- **Special precautions for user** Warning: Flammable liquids

- **Danger code (Kemler):** 33

- **EMS Number:** F-E, S-D

- **Stowage Category** E

- **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

- **Transport/Additional information:**

- **ADR**

- **Excepted quantities (EQ)** Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml

- **IMDG**

- **Limited quantities (LQ)** 1L
- **Excepted quantities (EQ)** Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml

- **UN "Model Regulation":** UN 1090 ACETONE SOLUTION, 3, II

CA

(Contd. on page 10)

Safety Data Sheet

according to HPR, Schedule 1

Printing date 05/13/2019

Version CA-EN-Rev 1

Reviewed on 05/13/2019

Trade name: GC Acrylic Primer

(Contd. of page 9)

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Canadian substance listings:

- **Canadian Domestic Substances List (DSL)**

acetone

methyl methacrylate (MMA)

synergist**

butylated hydroxytoluene

photoinitiator**

- **Canadian Ingredient Disclosure list (limit 0.1%)**

None of the ingredients is listed.

- **Canadian Ingredient Disclosure list (limit 1%)**

acetone

methyl methacrylate (MMA)

- **GHS label elements**

Exempt from classification and labeling – devices and drugs are not regulated according to WHMIS 2015.

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



- **Signal word** Danger

- **Hazard-determining components of labeling:**

acetone

methyl methacrylate (MMA)

urethane dimethacrylate (UDMA)

- **Hazard statements**

Highly flammable liquid and vapour.

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

May cause respiratory irritation. May cause drowsiness or dizziness.

Causes damage to organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

- **Precautionary statements**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Immediately call a poison center/doctor.

Specific treatment (see on this label).

Do NOT induce vomiting.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Take off contaminated clothing and wash it before reuse.

(Contd. on page 11)

Safety Data Sheet

according to HPR, Schedule 1

Printing date 05/13/2019

Version CA-EN-Rev 1

Reviewed on 05/13/2019

Trade name: GC Acrylic Primer

(Contd. of page 10)

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

- **Department issuing SDS:** Regulatory Affairs

- **Contact:**

Regulatory Affairs

Telephone No. +1 (708) 597-0900

SDS.gcamerica@gc.dental

- **Date of the latest revision of the safety data sheet** 05/13/2019 / -

- **Abbreviations and acronyms:**

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

HCS: Hazard Communication Standard (USA)

MSDS: Material Safety Data Sheet

SDS: Safety Data Sheet

ECHA: European Chemicals Agency

OSHA: Occupational Safety and Health Administration (USA)

TDG: Transportation of Dangerous Goods (Canada)

LEL: Lower Explosive Limit

UEL: Upper Explosive Limit

AwSV: Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (Ordinance on facilities for handling substances that are hazardous to water) (Germany)

NOEC: No-Observed-Effect Concentration

IMDG Code: International Maritime Dangerous Goods Code

DOT: Department of Transportation (USA)

IATA: International Air Transport Association

CAS: Chemical Abstracts Service (division of the American Chemical Society)

WHMIS: Workplace Hazardous Materials Information System (Canada)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

- **Sources**

- Manufacturers' MSDSs/SDSs

- OSHA (<https://www.osha.gov/dts/chemicalsampling/toc/chmcas.html>)

- TOXNET (<http://toxnet.nlm.nih.gov/>)

- ECHA (<http://echa.europa.eu/>)

- EnviChem (www.echemportal.org)

- **Notes:**

CAS Registry Number® is a Registered Trademark of the American Chemical Society.

CHEMTRAC® is a registered service mark of the American Chemistry Council, Inc.

- **Disclaimer:**

The information contained herein is believed to be true and accurate. However, all statements, recommendations or suggestions are made without any guarantee, representation or warranty, express or implied, on our part. Therefore, no warranty is made or to be implied that the information set out in this document is accurate or complete, and we accordingly exclude all liability in connection with the use of this information or the products referred to herein. All such risks are assumed by the purchaser/user. The information contained herein is also subject to change without notice. For the avoidance of doubt, however, nothing in this document excludes or limits our liability for death or personal injury caused by our negligence or for fraudulent misrepresentation.